

Cartucce GPL

05100/FK

Cartuccia universale perforabile.
Conforme alla norma EN 417.
Contenuto: 190 gr. di gas Butano.
Pressione: a 15° C ~ 1,5 bar / a 50° C ~ 5 bar.

Cartouche de gaz universelle perforable.
Conforme à la Norme EN 417.
Contenu: 190 gr. de gaz Butane.
Pression: à 15° C ~ 1,5 bar / à 50° C ~ 5 bar.

Universal pierceable gas cartridge.
 Complying with EN 417 specification.
 Contents: 190 gr. of Butane gas.
 Pressure: at 15° C ~ 1,5 bar / at 50° C ~ 5 bar.



MASTER PACK
 cm. 36,5x28x26
 kg. 10,5
 N. 36



CONTAINER
 1x20'
 N. 38160

05120-05140

Cartucce con attacco 7/16" conformi alla Norma EN417.
Contenuto: miscela di gas Butano (70%) - Propano (30%).
Pressione: a 15° C ~ 2,7 bar / a 50° C ~ 7,7 bar.

Cartouches à gaz avec connexion 7/16" conformément à la norme EN417.
Contenu: mélange de gaz Butane (70%) - Propane (30%).
Pression: a 15° C ~ 2,7 bar / a 50° C ~ 7,7 bar.

Gas cartridges with 7/16" connection complying with EN417 specification.
 Contents: mixture of Butane gas (70%) and Propane gas (30%).
 Pressure: at 15° C ~ 2,7 bar / at 50° C ~ 7,7 bar.



Art.	G30/G31 gr.	Master pack	Container
05120	220	cm. 43x32x10 - kg. 3,8 n. 12	24600
05130	330	cm. 21x28x27,5 - kg. 6 n. 12	21000
05140	430	cm. 43x32x10 - kg. 6,4 n. 12	13800